





RoHS
Compliant
2002/95/EC



REV.	ECN.	NO.	APPD.

DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.15 ± 0.1mm
Operating Force	160±50gf
Operating Life(cycles)	100,000

.X ±0.2

X. ±2°

UNITS mm

MAT'L


SEE NOTE

FINISH

SEE NOTE

Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.



LONGCHUANG ZHONGYE (HK)CO.,LIMITED

TITLE:

TACT SWITCH

PART NO.:

AT-1100AANP SERIES

DR:

Ricky 2015/03/17

DWG NO.:

ASI-1100AANP

CHKD:

Ricky 2015/03/17

APPD:

SCALE

1:1

SHEET

1/1

REV.

A

CUSTOMER

DRAWING