




REV.	ECN.	NO.	APPD.

[illegible]

SW 10-02 X-XX

1 2 3 4 5



CIRCUIT DIAGRAM

- 1.Series : SW
- 2.Current Rating : 10=10A 125/250VAC
- 3.Actuator : 00=Non-lever 01-99=Lever
- 4.Termination : see chart (N/P/A)
(7=SPST-NO / 3=SPST-NC)
- 5.Operating Force : see chart

1.1 Rated Voltage(AC)	125/250VAC	
1.2 Rated Current(AC)	10.1A	
1.3 Contact Resistance	≤100mΩ(Initial value)	
1.4 Operating Force	40±20gf	55±25gf
1.5 Bounce Time		
1.6 Free Position	18.0±1.2mm	
1.7 Operating Position	13.8±1.2mm	
1.8 Position Travel		
1.9 Return Force		

2.1 Mechanical Life	1,000,000 CYCLES
2.2 Electrical Life	6,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC500V(Initial value)
2.4 Withstand Voltage	AC1000V 1 minute(Initial value)
2.5 Soldering Technic	Hand Soldering
2.6 Operating Temper	−25°C ~ +85°C
2.7 Ambient Humidity Used	<85%RH

Tolerance: ±0.2		UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED				
		MAT'L	TITLE:		PART NO:		
		SEE NOTE	MICRO SWITCH SM10 SERIES		SM10-02N-XX		
		FINISH	DR: <i>Ricky</i> 2017/4/7		DWG NO:		
		SEE NOTE	CHKD: <i>Ricky</i> 2017/4/7		ATD-02X-XX		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.		Q'TY	APPD:		SCALE	SHEET	REV.
					1:1	1/2	A
					CUSTOMER DRAWING		

