


DIMENSIONS



1.Functional spec

1.1 Rated Voltage	125VAC/DC5V
1.2 Rated Current	1A/30mA
1.3 Contact Resistance	≤100mΩ(initial value)
1.4 Operating Force	30(20~50gf)
1.5 Bounce Time	40±20gf
1.6 Free Position	12.8±0.8mm
1.7 Operating Position	10.8±0.8mm
1.8 Position Travel	
1.9 Return Force	

2.Reliable Rating


2.1 Mechanical Life	1,000,000 CYCLES
2.2 Electrical Life	10,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC500V
2.4 Withstand Voltage	AC500V 1 minute
2.5 Soldering Technic	Hand Soldering
2.6 Operating Temper	−25°C ~ +65°C
2.7 Ambient Humidity Used	<85%RH

MODEL CODE

DM 1-02X-XX-3
1 2 3 4 5 6

- 1.Series : DM
- 2.Current Rating : 1=1A 125VAC ; 30mA DC5V
- 3.Actuator : 00=non-lever 01=99=Lever
- 4.Termination : see chart (P/C/D/T/N)
- 5.Operating Force: see chart
- 6.Button colour : 3=white
- 7.Cover type : No-0=have two lines

CIRCUIT DIAGRAM



Tolerance:±0.2	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
	MAT'L	TITLE:	PART NO.:		
	SEE NOTE	MICRO SWITCH DM SERIES	DM1-02P-XX-3		
	FINISH	DR: Ricky 2017/2/17	DWG NO.:	ATD-02X-XX-3	
	SEE NOTE	CHKD: Ricky 2017/2/17	SCALE	SHEET	REV.
	Q'TY	APPD:	11	1/2	A
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN CONSENT OF ACCURATE INNOTECH INC.					
					CUSTOMER DRAWING