REV.	ECN. NO.	APPD.

RoHS Compliant 2002/95/EC

Process Capable

DIMENSIONS



MODEL CODE:

DCB0-0167B- B □ PB BK S 0 4

(1) (2) (3)(4) (5) (6) (7)(8) (9)

(1):Series type:DC POWER JACK.
(2):Series No.
(3):Schematic option: B
(4):Center pin diameter:
G=ø1.65 , H=ø2.0 , J=ø2.5
(5):Material of housing:
10=PA10T , PB=PBT
(6):Housing color:
BK=Black
(7):Terminal plating
S=Silver(Ag)
(8):Special option:
0= Ni Plating for Center Pin(RoHS)
1= CuSn Plating for Center Pin(RoHS)
(9):Packing mode:
4=Bag packing

SPECIFICATION:

1.Rating : DC 20V 5A;
2.Contact resistance: ≤30mΩ;
After test:≤50mΩ
3.Insulation resistance: ≥100MΩ (DC500V);
After test:≥50MΩ
4.Withstand voltage: 500VAC;
5.Insertion and extraction force: 3-30N;
6.life test: 5,000 cycles;
7.Operation temperature range:-20°C~70°C;
8.Preservative temperature range:-40°C~85°C;





Model No.	G	H	J
CENTER PIN	ø1.65	ø2.0	ø2.5

○: ITEM NO. □: TERMINAL NO.

NO.	PARTS	MATERIAL	Q'TY	FINISHING
⑥	Ground Terminal	Stainless steel	1	Nickel plating
⑤	Shield plate	Stainless steel	1	
④	Peg	Copper Alloy	1	Tin plating
③	Tip spring [2]	Copper Alloy	1	Silver plating
②	Center pin [1]	Zinc Alloy	1	Ni/CuSn Plating
①	Housing	Thermoplastic	1	Black

TOLERANCE	ANGLES
.X ±0.50	X ±5°
.XX ±0.30	.X ±3°
.XXX ±0.15	.XX ±2°

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

UNITS mm
MAT'L SEE NOTE
FINISH SEE NOTE
Q'TY

LONGCHUANG ZHONGYE (HK)CO.,LIMITED

TITLE: DC POWER JACK	PART NO.: DCB0-0167B
DR: Ricky 2019/05/06	DWG NO.: AB0-0167B
CHKD: Ricky 2019/05/06	SCALE 1:1 / SHEET 1/1 / REV. A / CUSTOMER DRAWING
APPD:	

龙创中业 开关 | 插座 | 连接器 LCZY SWITCH