





- NOTES:
1. ELECTRICAL:
- 1) VOLTAGE CURRENT RATING:2AMP,30V AC;
 - 2) INSULATION RESISTANCE: 1000MΩ MIN;
 - 3) CONTACT RESISTANCE: 30mΩ MAX;
 - 4) WITHSTANDING VOLTAGE: 500V AC;
 - 5) OPERATING TEMPERATURE:-55°C TO +85°C.
2. Mechanical:
- 1) Mating Force: 35N MAX
 - 2) Unmating Force: 10N MIN.
3. NOTE:1.DIMENSIONS MARKED "▼"
TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04*N-1*R627

1: Au 1U"
6: Au 30U"

W: WHITE
B: BLACK

1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

3	HOUSING	PBT	1	UL94V-0	X: ±0.35	X: ±2"	UNITS	LONGCHUANG ZHONGYE (HK)CO.,LIMITED					
					X ±0.3	X' ±1"	MAT'L						mm
							SEE NOTE						
							FINISH						
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XX ±0.25	.XX"		SEE NOTE	DR: <i>Rocky</i> 2014/04/29	PART NO.: USAF-04*N-1*R627			
					.XXX ±0.15	.XXX"		SEE NOTE	CHKD: <i>Rocky</i> 2014/04/29	DWG NO.: All-R627			
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF ACCURATE INNOTECH INC.			Q'TY	APPD:	SCALE	SHEET	REV.	CUSTOMER DRAWING
NO	PARTS	MATERIAL	QTY	FINISHING						1:1	1/1	B	

E

D

C

B

A

E

D

C

B

A