

RoHS

Height(高度):NO.1

8.0	J		T
7.5	I		S
7.0	H		R
6.5	G		Q
6.0	F	11.0	P
5.5	E	10.5	O
5.0	D	10.0	N
4.8	C	9.5	M
4.5	B	9.0	L
4.3	A	8.5	K
高度H(mm)	X=	高度H(mm)	X=

Material:

Button 按钮	PPA/LCP
Cover plate 盖板	铁(镀银)
Shrapnel 弹片	不锈钢(复银)
Base 基座	PPA/LCP
Pin 引脚	磷铜(镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA
Contact impedance(接触阻抗):	≤100mΩMAX
Insulation impedance(绝缘阻抗):	≥100MΩMIN
Welding resistance temperature(耐焊温度):	250±5°5s
OPERATING LIFE(电气寿命):	100,000 cycles
Usage temperature(使用温度):	-25 to 85
Operating humidity(使用湿度):	≤85% RH
Trip(行程):	0.25±0.1mm
Operating force(操作力):	1 90±30gf 2 130±30gf 3 180±50gf 4 250±50gf 5 350±50gf 6

NO.2

public errand(公差):±0.2mm unit(单位):mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K2-1109SE			CHECK	Z.LIU	REV.	A1
UNIT:	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	K2-09-2019
mm	OTHERWISE	ABOVE 5~30	±0.3	0°±3°	SCALE	PAGE	1 OF 1
		ABOVE 30	±0.5				
		ANGLE	±3°				

K2-1109SE-□-□

