

RoHS

Height(高度) :NO.1

11.0	J		T
10.5	I		S
10.0	H		R
9.5	G		Q
9.0	F		P
8.5	E		O
8.0	D		N
7.5	C		M
7.0	B	12.0	L
6.5	A	11.5	K
高度H (mm)	X=	高度H (mm)	X=

Material: 防水等级IP67

Button 按钮	PBT/LCP耐温280°C
Cover plate 盖板	铁 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 基座	PBT/LCP耐温280°C
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA
Contact impedance(接触阻抗):	≤100mΩMAX
Insulation impedance(绝缘阻抗):	≥100MΩMIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE (电气寿命):	100,000 cycles
Usage temperature (使用温度):	-25 °C to 85 °C
Operating humidity (使用湿度):	≤85% RH
Trip(行程):	0.35±0.1mm
Operating force(操作力):	1 90±30gf 2 130±30gf 3 180±50gf 4 250±50gf 5 350±50gf 6

NO.2

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K2-1843DP			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE	UP TO 5	ANGLE	APPROVAL	DATE	K2-09-2019
	mm	OTHERWISE	ABOVE 5 ~30				
			ABOVE 30	0°±3°	SCALE	PAGE	1 OF 1
			ANGLE				

K2-1843DP-□-□