

RoHS

Height(高度): NO.1

10.5	J	16.0	T
10.0	I	15.0	S
9.5	H	14.5	R
9.0	G	14.0	Q
8.5	F	13.5	P
8.0	E	13.0	O
7.5	D	12.5	N
7.0	C	12.0	M
6.5	B	11.5	L
6.0	A	11.0	K
高度H(mm)	X=	高度H(mm)	X=

Material: 防水等级IP67

Button 按钮	PBT/LCP耐温280
Cover plate 盖板	铁(镀银)
Shrapnel 弹片	不锈钢(复银)
Base 基座	PBT/LCP耐温280
Pin 引脚	磷铜(镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA			
Contact impedance(接触阻抗):	≤ 100mΩ MAX			
Insulation impedance(绝缘阻抗):	≥ 100MΩ MIN			
Welding resistance temperature (耐焊温度):	250 ± 5 ° 5s			
OPERATING LIFE (电气寿命):	100,000 cycles			
Usage temperature (使用温度):	-25 to 85			
Operating humidity (使用湿度):	≤ 85% RH			
Trip(行程):	0.35 ± 0.1mm			
Operating force(操作力):	1	90 ± 30gf	2	130 ± 30gf
	3	180 ± 50gf	4	250 ± 50gf
	5	350 ± 50gf	6	

NO.2

NO.2

public errand(公差): ±0.2mm unit(单位): mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		G.L CHEN		DWG.No.		LCZY	
PART NO.		K2-1843SP		CHECK		Z.LIU		REV.		A1	
	UNIT:	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5 ~ 30 ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3°	ANGLE 0° ± 3°	APPROVAL		DATE		K2-09-2019	
						SCALE		PAGE		1 OF 1	

K2-1843SP-□-□