




RoHS



P.C.B LAYOUT(Copper-side view)



Model No.	1	2	3
PIN	Ø2.0	Ø2.35	Ø2.5

public errand (公差) : ±0.2mm unit (单位) : mm

Material:

contact pin插针	Au
plastic cement塑胶	Nylon尼龙/PA46
Pin 引脚	Au
CONTACT A(P脚A)	Au

Main technical specifications:

Rated load(额定负荷):	DC30V 0.5A
Contact impedance(接触阻抗):	≤100mΩMAX
Insulation impedance(绝缘阻抗):	≥100MΩMIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE(电气寿命):	5,000 cycles
Usage temperature(使用温度):	-20 °C to 70 °C
Operating humidity(使用湿度):	≤85% RH
Insertion and Extraction Force(插拔力)	3~20N
	1 2
	3 4
	5 6

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	DC JACK			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	DC-005			CHECK	Z.LIU	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	APPROVAL	DATE	DC-09-2019	
		ABOVE 5 ~30	±0.3				
mm	OTHERWISE	ABOVE 30	±0.5	SCALE	PAGE	1 OF 1	
		ANGLE	±3°				

DC-005-□